

Pipe Safety Railings

Protect people from uneven walkways and mezzanine drop offs. These durable railings are made of schedule 40 pipe (1-5/8" O.D.). Handrails are 42" high with a 21" mid-rail. Mounting options include socket sleeves, cast steel base, barricade base, or cast steel sockets for convenient handrail removal. The cast steel sockets accept wood 2" x 4" or 2" x 6" when toe boards are required. The cast steel base has two lag down holes for permanently mounting the railing. There are two open cavities to allow for 2" x 4" or 2" x 5" toe boards. Steel railing features powder coat safety yellow finish.

STEEL CONSTRUCTION					
MODEL NUMBER	TOP RAIL HEIGHT	MIDRAIL HEIGHT	LENGTH	OUTSIDE DIAMETER	NET WT. (POUNDS)
VDKR-2	42"	21"	24"	1-5/8"	18/UPS
VDKR-3	42"	21"	36"	1-5/8"	23/UPS
VDKR-4	42"	21"	48"	1-5/8"	28
VDKR-5	42"	21"	60"	1-5/8"	33
VDKR-6	42"	21"	72"	1-5/8"	38
VDKR-7	42"	21"	84"	1-5/8"	43
VDKR-8	42"	21"	96"	1-5/8"	48
ALUMINUM CONSTRUCTION					
ADKR-2	42"	21"	24"	1-5/8"	9/UPS
ADKR-3	42"	21"	36"	1-5/8"	10/UPS
ADKR-4	42"	21"	48"	1-5/8"	11
ADKR-5	42"	21"	60"	1-5/8"	13
ADKR-6	42"	21"	72"	1-5/8"	15
ADKR-7	42"	21"	84"	1-5/8"	16
ADKR-8	42"	21"	96"	1-5/8"	18
PIPE SAFETY RAILING OPTIONS					
MODEL NUMBER	DESCRIPTION				NET WT. (POUNDS)
VDKR-P101	SINGLE SOCKET (FOUR BOLT HOLES)				7
VDKR-P102	DOUBLE SOCKET (FOUR BOLT HOLES)				12
VDKR-BASE	CAST STEEL BASE				115
VDKR-P107	4" METAL SLEEVE				2
VDKR-BB-F	BARRICADE BASE WITH FEET				7
VDKR-BB-W	BARRICADE BASE WITH WHEELS				7
VDKR-G3	THREE FOOT STEEL GATE				23
VDKR-G4	FOUR FOOT STEEL GATE				35
VDKR-KIT	ANCHOR BOLTS FOR CONCRETE (4) 3/8" x 3"				4
VDKR-CON	CONNECTOR KIT				7

RAILING OPTIONS WORK WITH BOTH STEEL & ALUMINUM RAILING

Crowd Control Interlocking Barriers

Lightweight one-piece handrail is attractive and functional. Interlocking portable railing has many commercial and industrial applications. Easy to move to meet changing needs. Upright bars are vertically spaced at 5¼" intervals. Includes connectors to attach multiple units together to form long runs. Overall size is 102"L x 40"H. All welded steel construction available with a galvanized or yellow powder coat finish. Suffix-HD denotes heavy duty construction.

MODEL NUMBER	FINISH	RAIL DIAMETER	NET WT. (LBS.)
PRAIL-102-G	GALVANIZED	1-1/4"	36
PRAIL-102-HD-G	GALVANIZED	1-5/8"	56
PRAIL-102-Y	YELLOW POWDER COAT	1-1/4"	36
PRAIL-102-HD-Y	YELLOW POWDER COAT	1-5/8"	56

Stainless Steel Railing

Keep guests flowing in restaurants, schools, offices or other indoor, and outdoor applications. The unique contemporary design offers a clean look wherever the railing is placed. The free standing units won't rust. Railing includes weighted round base feet, which may easily be removed for storage, and chain interlocking system for attaching multiple units together to form long runs.

MODEL NUMBER	LENGTH	HEIGHT	BASE DIAMETER	NET WT. (POUNDS)
SSRAIL-96	96"	42"	12"	55



STEEL PIPE SAFETY RAILING • series VDKR
shown with optional sockets




CONNECTOR KIT
Includes (2) male & (2) female connectors
model VDKR-CON


POWDER COATED TOUGH
Steel Only




ALUMINUM PIPE SAFETY RAILING
series ADKR
shown with optional sockets




SINGLE SOCKET
for surface mounting, accepts wood for toeboards.
model VDKR-P101




DOUBLE SOCKET
for surface mounting. Sockets are 4" high and hold two posts.
model VDKR-P102




METAL SLEEVE
is used for concrete mount. Measures 4"H x 2" O.D.
model VDKR-P107



PERMANENT/
PORTABLE BASE
designed to meet OSHA temporary floor edge and roof railing requirements (OSHA 1926.500)
model VDKR-BASE



BARRICADE BASE
WITH FEET
model VDKR-BB-F



3 or 4 FOOT GATE
model VDKR-G3
model VDKR-G4
Hardware Included



model PRAIL-102-G



model PRAIL-102-Y



48 Hours
to Ship




WIRE MESH (welded)
FOR HANDRAIL
series WM



CONNECTION TUBING
series CSEC



PLASTIC BUMPER
model M-BUMP



60" SLIDING GATE
model S-GATE-60



CORNER CONNECTORS
model C-CON



CONCRETE ANCHOR BOLTS
model VDKR-KIT

Steel Square Safety Handrails

An economical way to protect people and machinery. Applications include loading docks, floor openings, walkways, and mezzanines. Highly visible safety yellow powder coat finish. Available with or without toeboards as application requires.

MODEL NUMBER	SQUARE TUBE (O.D.)	OVERALL HEIGHT	MID-RAIL HEIGHT	LENGTH	NET WT. (POUNDS)	
RIGID SECTION WITH TOEBOARD						
SQ-48-TB [Ⓢ]	1-5/8"	42"	21"	48"	59	
SQ-60-TB	1-5/8"	42"	21"	60"	64	
SQ-72-TB [Ⓢ]	1-5/8"	42"	21"	72"	67	
SQ-84-TB	1-5/8"	42"	21"	84"	72	
SQ-96-TB [Ⓢ]	1-5/8"	42"	21"	96"	76	
SQ-108-TB	1-5/8"	42"	21"	108"	80	
SQ-120-TB	1-5/8"	42"	21"	120"	84	
RIGID SECTION WITHOUT TOEBOARD						
SQ-48 [Ⓢ]	1-5/8"	42"	21"	48"	42	
SQ-60	1-5/8"	42"	21"	60"	48	
SQ-72 [Ⓢ]	1-5/8"	42"	21"	72"	50	
SQ-84	1-5/8"	42"	21"	84"	55	
SQ-96 [Ⓢ]	1-5/8"	42"	21"	96"	60	
SQ-108	1-5/8"	42"	21"	108"	66	
SQ-120	1-5/8"	42"	21"	120"	70	
OPTIONAL WIRE MESH (welded on)						
WM-48	--	22"	--	48"	18	
WM-60	--	22"	--	60"	25	
WM-72	--	22"	--	72"	28	
WM-84	--	22"	--	84"	32	
WM-96	--	22"	--	96"	36	
WM-108	--	22"	--	108"	41	
WM-120	--	22"	--	120"	43	
OPTIONAL CONNECTION TUBING (†)						
CSEC-48 [Ⓢ]	1-5/8"	--	--	48"	14/PR.	
CSEC-60	1-5/8"	--	--	60"	16/PR.	
CSEC-72 [Ⓢ]	1-5/8"	--	--	72"	18/PR.	
CSEC-84	1-5/8"	--	--	84"	20/PR.	
CSEC-96 [Ⓢ]	1-5/8"	--	--	96"	22/PR.	
CSEC-108	1-5/8"	--	--	108"	24/PR.	
CSEC-120	1-5/8"	--	--	120"	25/PR.	
OPTIONAL 4" HIGH TOEBOARD						
TOE-B-48 [Ⓢ]	--	4"	--	43½"	17	
TOE-B-60	--	4"	--	55½"	21	
TOE-B-72 [Ⓢ]	--	4"	--	67½"	25	
TOE-B-84	--	4"	--	79½"	30	
TOE-B-96 [Ⓢ]	--	4"	--	91½"	34	
TOE-B-108	--	4"	--	99"	36	
TOE-B-120*	--	4"	--	111"	42	
OPTIONS						
C-CON [Ⓢ]	CORNER CONNECTORS				10	
S-GATE-60	60" SLIDING GATE				22	
M-BUMP	72"L x 10"H BUMPER (HARDWARE INCLUDED)				43	
VDKR-KIT	CONCRETE ANCHOR BOLTS (4) 3/8" x 3"				4	


(†) CONNECTION TUBING IS PRICED & SOLD IN PAIRS

*RECEIVE (2) PIECES 55½" LONG EACH

Self-Closing Steel Gates

Customize your safety railings with Self-Closing Steel Gates. Gates can be mounted from the left or right with the included mounting hardware. Mount to horizontal rails that measure up to 2" diameter and are spaced 10" to 21" apart center to center. Choose from galvanized or yellow powder coat finish. Meets OSHA 1910.23a requirements. (Railing and base not included.)

MODEL NUMBER	MATERIAL	OPENING WIDTH	HEIGHT	NET WT. (POUNDS)	
SPG-26-Y	YELLOW	16" to 26"	12"	30	
SPG-26-G	GALVANIZED	16" to 26"	12"	30	
SPG-40-Y	YELLOW	24" to 40"	12"	35	
SPG-40-G	GALVANIZED	24" to 40"	12"	35	



Guard Rail Systems

Protect personnel and equipment both visually and physically with our Guard Rail Systems. These economical systems can be utilized indoors or outdoors. Ideal for protecting corners of buildings and machinery from fork truck and vehicle damage. Choose between one, two, or three high rail systems. Tubular posts are machined for continuous or perpendicular rail mounting. US D.O.T. guard rail mounting and I-beam posts available, contact factory. Rail mounting hardware included with post. Floor mounting kit sold separately. Deduct 5" when overlapping on a shared post.

MODEL NUMBER	HEIGHT	LENGTH	MOUNTING POSTS REQUIRED	RADIUS	NET WT. (POUNDS)
GALVANIZED GUARD RAIL - STRAIGHT RAILS					
GR-4	12"	48"	2	--	44
GR-6	12"	72"	2	--	66
GR-8	12"	96"	2	--	89
GR-10	12"	120"	3	--	112
GR-12	12"	144"	3	--	133
POWDER COAT GUARD RAIL - STRAIGHT RAILS					
GR-4-PC-YEL	12"	48"	2	--	44
GR-6-PC-YEL	12"	72"	2	--	66
GR-8-PC-YEL	12"	96"	2	--	89
GR-10-PC-YEL	12"	120"	3	--	112
GR-12-PC-YEL	12"	144"	3	--	133
GALVANIZED GUARD RAIL - CURVED RAILS 90°					
GR-4-CRV	12"	48"	2	30½"	44
GR-6-CRV	12"	72"	2	46"	66
GR-10-CRV	12"	120"	3	75½"	112
GR-12-CRV	12"	144"	3	91½"	133

GUARD RAIL OPTIONS				
MODEL NUMBER	DESCRIPTION	GUARD RAIL LEVELS	NET WT. (LBS.)	
GR-SP	SPRING POST - 24" HIGH	ONE	21	
GR-TP18	TUBULAR POST - 18" HIGH (10" x 10" base plate)	ONE	41	
GR-TP42	TUBULAR POST - 42" HIGH (10" x 10" base plate)	TWO	60	
GR-TP60	TUBULAR POST - 60" HIGH (10" x 10" base plate)	THREE	89	
GR-TP72	TUBULAR POST - 72" HIGH (10" x 10" base plate)	THREE	109	
TUBULAR POSTS FOR DROP IN DESIGN				
GR-TP18-DI	18" HIGH POST (10" x 10" base plate)	ONE	46	
GR-TP42-DI	42" HIGH POST (10" x 10" base plate)	TWO	65	
GR-TP60-DI	60" HIGH POST (10" x 10" base plate)	THREE	94	
GR-TP72-DI	72" HIGH POST (10" x 10" base plate)	THREE	114	
GR-BKT-DI	EXTRA POST MOUNTING BRACKET		5	
GR-CAP	PLASTIC END CAP 7"W x 13½"H x 4"D (Adds 3" to Length)		7	
GR-BG	BUFFER END GUARD 48"L x 16"H x 12½"D (Adds 28" to Length)		40	
GR-TG	FLARED END GUARD 27"L x 18"H x 10"D (Adds 18" to Length)		30	
GR-ABK	CONCRETE ANCHOR BOLTS (4) 3/4" x 4"		2	
GR-SPP	SPRING POST MOUNT PLATE FOR ASPHALT/BLACKTOP APPLICATIONS		3	


Structural Guard Rail Systems

Constructed of structural C-channel 11.5 lbs. per foot for maximum strength and protection. Railing can be removed in a matter of seconds. Features 10" x 10" base plate with (4) pre-drilled mounting holes. Available in custom lengths.


MODEL NUMBER	HEIGHT	LENGTH	NET WT. (POUNDS)
STRUCTURAL GUARD RAIL			
ST-GR-4	8"	48"	46
ST-GR-6	8"	72"	69
ST-GR-8	8"	96"	92
ST-GR-10	8"	120"	115
ST-GR-12	8"	144"	138
TUBULAR MOUNTING POSTS WITH DROP-IN STYLE BRACKET			
STGR-TP-18DI	18" HIGH POST (ACCOMMODATES 1 RAIL)		47
STGR-TP-42DI	42" HIGH POST (ACCOMMODATES 2 RAIL)		67
STGR-TP-60DI	60" HIGH POST (ACCOMMODATES 3 RAIL)		95
STGR-TP-72DI	72" HIGH POST (ACCOMMODATES 3 RAIL)		116
STGR-BKT-DI	EXTRA POST MOUNTING BRACKET		5



series GR




series GR-PC-YEL



series GR-CRV


TUBULAR POST
series GR-TPShown with Galvanized
Guard Rail and Plastic End Caps
SPRING POST
model GR-SPShown with
Galvanized Guard Rail
DROP-IN STYLE POSTS
series GR-TP-DIPLASTIC END CAP
model GR-CAPCONCRETE
MOUNTING KIT
model GR-ABKFLARED END GUARD
model GR-TGBUFFER END GUARD
model GR-BG

The above two End Guards can either be welded or bolted onto our Galvanized Guard Rail. Hardware not included.

STRUCTURAL GUARD RAIL
series ST-GRSTRUCTURAL GUARD POSTS AND BRACKETS
series STGR-TP-DI



DROP-IN STYLE
model (2) YGR-LO-4
model (2) YGR-TP42-S



BOLT-ON STYLE
model (2) YGR-LO-4, (1) YGR-TP42-S,
(1) YGR-TP42-C, (1) YGR-LO-6,
(1) YGR-TP18-S



series YGR-TP



model WEB-P-GL



model WEB-P



WALL MOUNTED BARRIER
model WEB-W



METAL BASE
series TSB-7M

BASIC BASE
series TSB-7B



FLOOR MOUNTED POST
model PCB-W-F



GROUND STAKE POST
model PCB-W-G



Structural Guard Rail - drop-in and bolt-on style

Create a modular system to protect equipment, inventory, and individuals from damage or injury with this highly visible powder coat yellow Structural Guard Rail. Triple ridge corrugated rails are constructed from 1/8" thick material, made for high impact resistance indoors or out. Posts are constructed of round corner 1/4" thick material. The steel base plate measures 10" square and is 5/8" thick. Bolts, anchors, washers, and nuts are provided with individual post sections. Concrete mounting kit is available separately.

Provide a strong barrier with easy accessibility with our Drop-In Style rails. Slide rail sections into post saddles for simple assembly. Each Drop-In Style rail section includes two brackets. Bolt-On Style rails are designed for permanent installation.

MODEL NUMBER	HEIGHT	LENGTH	MOUNTING POSTS REQUIRED	NET WT. (POUNDS)	
STRUCTURAL GUARD RAIL SECTION - DROP-IN STYLE (2 BRACKETS INCLUDED PER RAIL)					
YGR-LO-4	14½"	48"	2	54	
YGR-LO-6	14½"	72"	2	74	
YGR-LO-8	14½"	96"	2	94	
YGR-LO-10	14½"	120"	3	114	
STRUCTURAL GUARD RAIL SECTION - BOLT-ON STYLE					
YGR-B-4	14½"	48"	2	44	
YGR-B-6	14½"	72"	2	64	
YGR-B-8	14½"	96"	2	84	
YGR-B-10	14½"	120"	3	104	
YGR-TP18-S	18"	RIGID CENTER POST		40	
YGR-TP42-S	42"	RIGID CENTER POST		65	
YGR-TP18-C	18"	RIGID CORNER POST		40	
YGR-TP42-C	42"	RIGID CORNER POST		65	
YGR-ABK-4	Concrete Mounting Kit, (4) Lag Bolts			4	

Indoor Personnel Guidance Barriers

Keep lines flowing smoothly with economical personnel guidance barriers. Perfect for restaurants, offices, hospitals, schools, and banks. Ideal for indoor applications. Series WEB are not interchangeable with series TSB and TSBO.

Floor Mounted Barrier, model WEB-P-GL includes black fabric web with a white stripe. The self-retracting web extends up to 72". Web end will attach to another barrier.

Wall Mounted Barrier, model WEB-W includes black fabric web with white stripe. The self-retracting web extends up to 72". Web end will attach to wall-mounted receiver or another floor-mounted barrier.

Classic Tensabarrier® Web Barrier is seen around the world in various businesses and airports. Many belt colors and designs available.

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)	
WEB-P-GL	40"H POST W/WEB & SELF-REELING TOP (GOLD)	42	
WEB-P	40"H POST W/WEB & SELF-REELING TOP (BLACK)	42	
WEB-W	WALL MOUNT UNIT WITH RECEPTACLE	6	
TSB-7M	13½"D METAL BASE - 7'6"L x 40"H	26	
TSB-13M	13½"D METAL BASE - 13'L x 40"H	26	
TSB-NBM	13½"D METAL BASE - NO BELT/ 40" POST ONLY	26	
TSB-7B	13½"D BASIC BASE - 7'6"L x 40"H	26	
TSB-13B	13½"D BASIC BASE - 13'L x 40"H	26	
TSB-NBB	13½"D BASIC BASE - NO BELT/ 40" POST ONLY	26	

Plastic Chain Barricades

Portable and lightweight units are easy to position where needed most. Choose either floor-mount or ground-stake design depending on application. Chain simply snaps onto post hooks (two hooks per post). Three standard colors to choose from: white, yellow and black. Units are easy to assemble with snap-together parts. Posts are sold six (6) to a box. Chains sold in rolls (each).

MODEL NUMBER	DESCRIPTION	COLOR	DIAMETER	HEIGHT	NET WT. (LBS.)	
PCB-W-F	FLOOR MT'D POST	WHITE	2½"	38½"	19	
PCB-Y-F	FLOOR MT'D POST	YELLOW	2½"	38½"	19	
PCB-B-F	FLOOR MT'D POST	BLACK	2½"	38½"	19	
PCB-W-G	GROUND STAKE POST	WHITE	2½"	35"	22	
PCB-Y-G	GROUND STAKE POST	YELLOW	2½"	35"	22	
PCB-B-G	GROUND STAKE POST	BLACK	2½"	35"	22	
PCB-W-CN	CHAIN	WHITE	2" x 50 ft.	--	9	
PCB-Y-CN	CHAIN	YELLOW	2" x 50 ft.	--	9	
PCB-B-CN	CHAIN	BLACK	2" x 50 ft.	--	9	

Steel Pipe Safety Bollards

Bollards can be used both indoors and outdoors to protect work areas, racking and personnel. Powder coated safety yellow finish. Molded rubber caps are removable on 4½" and 5½" diameter units. Steel caps are welded on the 1¾" diameter units. Base plate measures 8" x 8", on the 4.5 and 5.5 units (5" x 5" on the 1¾" units), and include four (4) pre-drilled mounting holes. Mounting kits and replacement caps available. Welded steel construction.

MODEL NUMBER	DESCRIPTION	HEIGHT	OUTSIDE DIAMETER	NET WT. (LBS.)	
BOL-24-2 Ⓢ	STEEL PIPE BOLLARD	24"	1¾"	12	
BOL-36-2 Ⓢ	STEEL PIPE BOLLARD	36"	1¾"	15	
BOL-42-2 Ⓢ	STEEL PIPE BOLLARD	42"	1¾"	16	
BOL-48-2 Ⓢ	STEEL PIPE BOLLARD	48"	1¾"	22	
BOL-24-4.5 Ⓢ	STEEL PIPE BOLLARD	24"	4½"	34	
BOL-36-4.5 Ⓢ	STEEL PIPE BOLLARD	36"	4½"	45	
BOL-42-4.5 Ⓢ	STEEL PIPE BOLLARD	42"	4½"	50	
BOL-48-4.5 Ⓢ	STEEL PIPE BOLLARD	48"	4½"	56	
BOL-24-5.5 Ⓢ	STEEL PIPE BOLLARD	24"	5½"	42	
BOL-36-5.5 Ⓢ	STEEL PIPE BOLLARD	36"	5½"	57	
BOL-42-5.5 Ⓢ	STEEL PIPE BOLLARD	42"	5½"	69	
BOL-48-5.5 Ⓢ	STEEL PIPE BOLLARD	48"	5½"	78	
BOL-ABK-3 Ⓢ	CONCRETE ANCHOR BOLTS (4) 3/8" x 3" (1¾" DIA. BOLLARDS)			2	
BOL-ABK-4 Ⓢ	CONCRETE ANCHOR BOLTS (4) 3/4" x 4" (4½" & 5½" DIA. BOL.)			2	




POWDER
COATED
TOUGH

Surface Mounted Removable Steel Pipe Safety Bollards


Bollards can be used both indoors and outdoors to protect work areas, racking and personnel. Surface mounted steel base plate allows for quick and easy bollard removal. Steel base plate is bolted in place. Guard is easily inserted into base plate then locked in place. Base plate includes four pre-drilled mounting holes. Powder coated safety yellow finish. Molded rubber caps are removable. Base plate measures 8" x 8". Welded steel construction.

MODEL NUMBER	DESCRIPTION	HEIGHT	OUTSIDE DIAMETER	NET WT. (LBS.)	
BOL-RF-24-4.5	SURFACE MOUNTED BOLLARD	24"	4½"	36	
BOL-RF-36-4.5	SURFACE MOUNTED BOLLARD	36"	4½"	47	
BOL-RF-42-4.5	SURFACE MOUNTED BOLLARD	42"	4½"	52	
BOL-RF-48-4.5	SURFACE MOUNTED BOLLARD	48"	4½"	58	
BOL-RF-24-5.5	SURFACE MOUNTED BOLLARD	24"	5½"	44	
BOL-RF-36-5.5	SURFACE MOUNTED BOLLARD	36"	5½"	59	
BOL-RF-42-5.5	SURFACE MOUNTED BOLLARD	42"	5½"	71	
BOL-RF-48-5.5	SURFACE MOUNTED BOLLARD	48"	5½"	80	



POWDER
COATED
TOUGH

New



Jumbo Steel Pipe Bollards

Oversized steel pipe for maximum protection and strength. Bollards can be used both indoors and outdoors to protect work areas, racking and personnel. Base plate includes four pre-drilled mounting holes. Welded steel cap. Base plate measures 8" x 8". Heavy-duty welded steel construction. Powder coated safety yellow finish.

MODEL NUMBER	HEIGHT	OUTSIDE DIAMETER	BASE PLATE	NET WT. (POUNDS)	
JBOL-36-12	36"	12"		66	
JBOL-48-12	48"	12"		83	
BOL-ABK-4	CONCRETE ANCHOR BOLTS (4) 3/4" x 4"			2	



POWDER
COATED
TOUGH

New

Offset Steel Bollards

Unique design features offset base plate that won't interfere with traffic. The 8" x 8" base plate includes (4) pre-drilled mounting holes (mounting hardware is sold separately). Removable rubber top cap and black/yellow safety tape included. Heavy-duty welded steel construction with a powder coat safety yellow finish is standard.

MODEL NUMBER	HEIGHT	OUTSIDE DIAMETER	BASE PLATE	NET WT. (POUNDS)	
OBOL-35-4.5	35"	4½"	8" x 8"	32	
OBOL-47-4.5	47"	4½"	8" x 8"	41	
OBOL-53-4.5	53"	4½"	8" x 8"	46	
BOL-ABK-4	CONCRETE ANCHOR BOLTS (4) 3/4" x 4"			2	

POWDER
COATED
TOUGH



PROTECTIVE BARRIERS



CHROME PLATED
model CBOL-42-4



POUR IN PLACE
series BOLPP



REMOVABLE
series BOL-R



SELF STORING
model BOL-SS-42-5.5



REMOVABLE
ORNAMENTAL BOLLARD
model BOL-OR-40-BK



Chrome-Plated Steel Bollard

Improve the image of your facility while protecting people and equipment. Unit is made of steel and finished with an attractive bright chrome plating for a clean fresh look. A black plastic top cap is removable to fill the bollard with concrete for greater strength and stability. The mounting plate is pre-drilled with (4) ½" diameter holes for quick and easy installation.

MODEL NUMBER	HEIGHT	DIAMETER	BASE PLATE DIAMETER	NET WT. (POUNDS)	
CBOL-42-4	42"	4"	8"	27	
CBOL-ABK-3	CONCRETE ANCHOR BOLTS (4) 3/8" x 3"			2	

Pour In Place Bollards

Make your bollards permanent by setting them in concrete. The extra length of the Pour in Place Bollard allows you to maintain the needed height while fixing the bollard in concrete. Bollard comes with welded anchoring tabs and a removable cap so the bollard can be filled with concrete to increase its strength and durability. Powder coated yellow for high visibility.

MODEL NUMBER	USABLE HEIGHT	OVERALL HEIGHT	OUTSIDE DIAMETER	NET WT. (POUNDS)	
BOLPP-24-5.5	24"	34"	5½"	44	
BOLPP-36-5.5	36"	46"	5½"	59	
BOLPP-42-5.5	42"	52"	5½"	73	
BOLPP-48-5.5	48"	58"	5½"	88	

Removable Bollards

The Removable Bollard comes with a sleeve that can be set in concrete to hold the bollard. When access is needed into an area that is protected by the bollard, simply lift the bollard out of the sleeve. Replace the bollard in its sleeve to reinstate the protective barrier. Powder coated yellow for high visibility. Sleeve is included.

MODEL NUMBER	USABLE HEIGHT	OVERALL HEIGHT	BOLLARD DIAMETER	NET WT. (POUNDS)	
BOL-R-36-5.5	36"	46"	5½"	88	
BOL-R-42-5.5	42"	52"	5½"	96	
BOL-R-48-5.5	48"	58"	5½"	103	

Self Storing Bollard with Door & Lock

This unique bollard is designed to slide down into the ground or floor when not needed. Great for preventing access to parking areas. Each unit includes a sleeve that can be set in the ground with concrete. Bollard has a handle in the top to allow for easy lifting and lowering. Lift and twist to lock into raised position. Twist and lower to return to stored position. Includes locking tab for use with padlock (padlock not included) to prevent unauthorized operation. Steel construction with powder coat safety yellow finish.

MODEL NUMBER	USABLE HEIGHT	BOLLARD DIAMETER	NET WT. (POUNDS)	
BOL-SS-42-5.5	42"	4½"	163	

Removable Ornamental Steel Bollard

Provide an attractive yet functional barrier to vehicle access and parking. Bollards are 4½" in diameter while the rings make the overall diameter 6". Padlock not included. Powder coat black finish. Includes eyes for attaching chain or rope.

Model BOL-OR-40-BK, locks into galvanized steel socket that is cemented into the ground. When the bollard is removed, a cover plate protects the hole leaving no protrusion above the surface.

Model BOL-OR-40-BK-SM, fits into steel socket that is bolted to ground (mounting hdwr. not included).

MODEL NUMBER	MOUNTING	USABLE HEIGHT	BOLLARD DIAMETER	NET WT. (POUNDS)	
BOL-OR-40-BK	UNDERGROUND	40"	4½"	84	
BOL-OR-40-BK-SM	SURFACE	46½"	4½"	84	

Movable Bollard (with Wheels)

Movable Bollard provides a portable visual barrier when an area needs temporary protection. Ideal for use when keeping traffic out of a temporarily hazardous area or area under repair. Can be used indoors or outdoors. Mold-on-rubber wheels standard. Powder coated yellow for high visibility.

MODEL NUMBER	USABLE HEIGHT	OUTSIDE DIAMETER	WHEEL SIZE	NET WT. (POUNDS)	
BOL-MB-42-5.5	42"	5½"	10"	71	

Folding Bollard

Folding steel barrier post for parking control and security. Bollard is locked in the raised position with a padlock (padlock not included). When padlock is removed, bollard may be lowered to ground to allow for access. Base plate must be lagged to ground for proper installation (installation hardware not included). Steel construction. Powder coat yellow or galvanized finish.

MODEL NUMBER	DESCRIPTION	EXTENDED HEIGHT	COLLAPSED HEIGHT	BOLLARD DIAMETER	NET WT. (POUNDS)	
BOL-FD-36-Y	YELLOW	42"	4"	1¾"	20	
BOL-FD-36-G	GALVANIZED	42"	4"	1¾"	20	

Spring Loaded Steel Bollards

Designed to serve as a visual and audible warning to personnel. Unique spring-loaded design will bend and not break like rigid bollards. Prevents damage to bollard and equipment. Promotes long life. Order bollard with or without light/siren option. Light/siren option includes sensitive switches that will activate a strobe light and warning siren when contacted. Operates with two 9V batteries (not included). Simply slides into open top of bollard. Each bollard is manufactured from steel and includes a powder coat safety yellow finish. Bollards measure 42" high with a 2½" O.D.

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)	
SPBOL-42 Ⓢ	SPRING BOLLARD	19	
SPBOL-42-BL Ⓢ	SPRING BOLLARD W/ BEEPER & STROBE	32	
SPBOL-ABK Ⓢ	CONCRETE ANCHOR BOLTS (3) 3/8" x 3"	2	

Smokers Bollards

Heavy-duty steel bollard also functions as a cigarette disposal unit. Cigarette disposable hole measures 1¼" diameter. Removable top is connected to steel container for holding cigarette butts. Top is lockable with padlock (padlock not included). Includes a durable powder coat safety yellow finish. Base plate includes four pre-drilled installation holes. Installation hardware sold separately. Optional dome base to hide installation bolts.

MODEL NUMBER	HEIGHT	OUTSIDE DIAMETER	BASE PLATE	NET WT. (POUNDS)	
BOL-SMK	35"	4½"	8" x 8"	32	
DOM-4.5 Ⓢ	3"	14"	--	8	
BOL-ABK-4 Ⓢ			CONCRETE ANCHOR BOLTS (4) 3/4" x 4"	2	

Smokers Stations

Keep smokers waste under control with these weather resistant, fire-safe, fade resistant, ADA compliant steel smoke stations. Oxygen restricting design quickly extinguishes cigarettes. Nylon base buttons prevent damage to surface and base. Top and base are connected with nickel plated brass chain to deter theft. Stainless steel latches for quick alignment when fastening. Factory Mutual Approved.

MODEL NUMBER	FINISH	HEIGHT	BASE DIAMETER	NET WT. (POUNDS)	
SMK-STA-B	BRONZE	39"	16"	20	
SMK-STA-C	CHARCOAL	39"	16"	20	



MOVABLE
model BOL-MB-42-5.5



FOLDING BOLLARD
model BOL-FD-36-Y



model SPBOL-42-BL



model BOL-SMK



series SMK-STA

Plastic Bollard

Permanent/Portable design Plastic Bollard features square shaped base and three reflective collars. 3" in diameter. Ideal for crowd control, in plant maintenance, and construction.

MODEL NUMBER	DESCRIPTION	OVERALL HEIGHT	BASE SIZE (W x L)	NET WT. (POUNDS)	
PBOL-32	HEAVY DUTY	31½"	14" x 14"	24	



MOLDED RUBBER
series BOL-CAP-R

Bollard Caps

Replace lost or damaged bollard caps. Easy to attach. Rubber cap has serrated tapered teeth for press-fit installation.

MODEL NUMBER	MATERIAL	INNER DIAMETER PIPE FITTING	FITS MODEL	NET WT. (POUNDS)	
BOL-CAP-4.5-R	MOLDED RUBBER	4.26" (4" SCH. 10 PIPE)	BOL-4.5	1	
BOL-CAP-5.5-R	MOLDED RUBBER	5.30" (5" SCH. 10 PIPE)	BOL-5.5	1	



Bollard/Post Covers

This durable poly sleeve will minimize maintenance and improve appearance. Covers are 1/8" thick. Units slide over existing bollards. No hardware needed.

MODEL NUMBER	HEIGHT	OUTSIDE DIAMETER	INSIDE DIAMETER	NET WT. (POUNDS)	
BPC-4	52"	5"	4-7/8"	5	
BPC-7	52"	7-1/8"	7"	6	



Plastic Bollard Covers

Eliminate the need for costly scraping and painting of unsightly bollards. The low density polyethylene thermoplastic molded sleeves slide over existing bollards. Covers are 1/4" thick. No hardware needed. Additional sizes, thicknesses, and colors available. Contact factory.

MODEL NUMBER	USE WITH MODEL	HEIGHT	INSIDE DIAMETER	NET WT. (POUNDS)	LIST PRICE EACH	
BPC-24-4.5	BOL-24-4.5	24"	4-13/16"	4	\$54.00	
BPC-36-4.5	BOL-36-4.5	36"	4-13/16"	6	54.00	
BPC-42-4.5	BOL-42-4.5	42"	4-13/16"	8	54.00	
BPC-24-5.5	BOL-24-5.5	24"	5-7/8"	6	\$60.00	
BPC-36-5.5	BOL-36-5.5	36"	5-7/8"	9	60.00	
BPC-42-5.5	BOL-42-5.5	42"	5-7/8"	11	60.00	



Decorative Bollard Covers

Improve the overall appearance of your facility for customers, strategic partners, or investors who come by to tour the facility. An excellent, affordable way of polishing the place up for important guests. Eliminate painting your bollards again. These 1/4" thick polyethylene thermoplastic material slides over your existing steel bollard. Many different styles and colors to choose from.

TYPE	MODEL NUMBER	HEIGHT	FITS PIPE DIAMETER	NET WT. (POUNDS)	
A	BPC-M-6-52-SC	52"	6" to 6 ⁵ / ₈ "	10	
B	BPC-M-LGT-6-52-SC	52"	6" to 6 ⁵ / ₈ "	10	
C	BPC-ARCH-6-52-TXT-SC	52"	6" to 6 ⁵ / ₈ "	9	
D	BPC-PAWN-11-49-SC*	49"	10" to 11"	24	
E	BPC-CINCO-11-52-SC*	52"	10" to 11"	18	
F	BPC-RIB-1-52-SC*	52"	10" to 11"	24	


*INSERTS AVAILABLE TO FIT 6" & 8" MODELS

STANDARD COLOR			
COLOR		COLOR	
	FOREST GREEN		RED
	BLACK		GREY

Protective Dome Covers for Bollards

Prevent accidents and injuries from people tripping over raised bolts. Easy to use device slides over bollards covering mounting hardware and base plate for a nice clean finish. Durable yellow powder coat finish. Steel construction. No hardware required.

MODEL NUMBER	USE WITH	OUTSIDE DIAMETER	HEIGHT	NET WT. (POUNDS)	
DOME-4.5 Ⓢ	4½" DIAMETER BOLLARDS	14"	3"	8	
DOME-5.5 Ⓢ	5½" DIAMETER BOLLARDS	14"	3"	9	



Plastic Hardware Caps for Bollards

Plastic hardware caps snap over the top of anchor bolts and washers to protect from weathering. Caps also provide for a cleaner look.


MODEL NUMBER	DESCRIPTION	QUANTITY PER PACKAGE	NET WT. (POUNDS)	
BC-B-1.5	SNAPS OVER ANCHOR HARDWARE	4	1	



Low Profile Rack Guards

May be used either indoors or outdoors to protect valuable pallet racking, machinery, and personnel. High visibility yellow powder coat finish. Heavy-duty welded steel construction.

MODEL NUMBER	DESCRIPTION	HEIGHT	LENGTH	OUTSIDE DIAMETER	NET WT. (POUNDS)	
LPRO-36-9-2 Ⓢ	LOW PROFILE GUARD	9"	36"	1-5/8"	22/UPS	
LPRO-48-9-2 Ⓢ	LOW PROFILE GUARD	9"	48"	1-5/8"	26/UPS	
LPRO-36-16-2 Ⓢ	LOW PROFILE GUARD	16"	36"	1-5/8"	28/UPS	
LPRO-48-16-2 Ⓢ	LOW PROFILE GUARD	16"	48"	1-5/8"	32/UPS	
LPRO-36-9-4 Ⓢ	LOW PROFILE GUARD	9"	36"	4-1/2"	48/UPS	
LPRO-48-9-4 Ⓢ	LOW PROFILE GUARD	9"	48"	4-1/2"	60/UPS	
LPRO-36-16-4 Ⓢ	LOW PROFILE GUARD	16"	36"	4-1/2"	64/UPS	
LPRO-48-16-4 Ⓢ	LOW PROFILE GUARD	16"	48"	4-1/2"	73/UPS	
LPRO-ABK-3 Ⓢ	CONCRETE ANCHOR BOLTS (8) 3/8" x 3" (1-5/8" DIA.)				4	
LPRO-ABK-4 Ⓢ	CONCRETE ANCHOR BOLTS (8) 3/4" x 4" (4-1/2" DIA.)				4	




High Profile Machinery Guards

Heavy-duty steel construction for protecting racks, building walls, expensive equipment, and hundreds of other applications. All 42" high units include a 21" mid-rail to comply with OSHA handrailing requirements. Two base plates with four pre-drilled mounting holes in each plate. Welded steel construction.


MODEL NUMBER	DESCRIPTION	HEIGHT	LENGTH	OUTSIDE DIAMETER	NET WT. (POUNDS)	
HPRO-36-24-2 Ⓢ	HIGH PROFILE GUARD	24"	36"	1-5/8"	30/UPS	
HPRO-48-24-2 Ⓢ	HIGH PROFILE GUARD	24"	48"	1-5/8"	40/UPS	
HPRO-36-36-2 Ⓢ	HIGH PROFILE GUARD	36"	36"	1-5/8"	38	
HPRO-48-36-2 Ⓢ	HIGH PROFILE GUARD	36"	48"	1-5/8"	48	
HPRO-36-42-2 Ⓢ	HIGH PROFILE GUARD	42"	36"	1-5/8"	42	
HPRO-48-42-2 Ⓢ	HIGH PROFILE GUARD	42"	48"	1-5/8"	52	
HPRO-36-24-4 Ⓢ	HIGH PROFILE GUARD	24"	36"	4-1/2"	53/UPS	
HPRO-48-24-4 Ⓢ	HIGH PROFILE GUARD	24"	48"	4-1/2"	69/UPS	
HPRO-36-36-4 Ⓢ	HIGH PROFILE GUARD	36"	36"	4-1/2"	74	
HPRO-48-36-4 Ⓢ	HIGH PROFILE GUARD	36"	48"	4-1/2"	82	
HPRO-36-42-4 Ⓢ	HIGH PROFILE GUARD	42"	36"	4-1/2"	89	
HPRO-48-42-4 Ⓢ	HIGH PROFILE GUARD	42"	48"	4-1/2"	93	
HPRO-ABK-3 Ⓢ	CONCRETE ANCHOR BOLTS (8) 3/8" x 3" (1-5/8" DIA.)				4	
HPRO-ABK-4 Ⓢ	CONCRETE ANCHOR BOLTS (8) 3/4" x 4" (4-1/2" DIA.)				4	





New

POWDER
COATED
TOUGH™




Surface Mounted Removable High Profile Machinery Guards & Low Profile Rack Guards

Surface-mounted steel base plates allow for quick and easy guard removal. May be used either indoors or outdoors. Steel base plates are bolted in place. Guard is easily inserted into base plates then locked into place. Base plate includes four pre-drilled mounting holes. Welded steel construction with yellow powder coat finish.

MODEL NUMBER	DESCRIPTION	HEIGHT	LENGTH	OUTSIDE DIAMETER	NET WT. (POUNDS)	
HIGH PROFILE MACHINERY GUARDS						
HPRO-RF-36-24-4	HIGH PROFILE GUARD	24"	36"	4-1/2"	57/UPS	
HPRO-RF-48-24-4	HIGH PROFILE GUARD	24"	48"	4-1/2"	73/UPS	
HPRO-RF-36-36-4	HIGH PROFILE GUARD	36"	36"	4-1/2"	78	
HPRO-RF-48-36-4	HIGH PROFILE GUARD	36"	48"	4-1/2"	86	
HPRO-RF-36-42-4	HIGH PROFILE GUARD	42"	36"	4-1/2"	93	
HPRO-RF-48-42-4	HIGH PROFILE GUARD	42"	48"	4-1/2"	97	
LOW PROFILE RACK GUARDS						
LPRO-RF-36-9-4	LOW PROFILE GUARD	9"	36"	4-1/2"	52/UPS	
LPRO-RF-48-9-4	LOW PROFILE GUARD	9"	48"	4-1/2"	64/UPS	
LPRO-RF-36-16-4	LOW PROFILE GUARD	16"	36"	4-1/2"	68/UPS	
LPRO-RF-48-16-4	LOW PROFILE GUARD	16"	48"	4-1/2"	77/UPS	

New



POWDER
COATED
TOUGH™

POWDER
COATED
TOUGH™

Floor Stop Bollard

Unique design offers horizontal crash protection. Unit is easily inserted into base plates then locked into place. Base plate includes four pre-drilled mounting holes. Removable black rubber end caps. Welded steel construction with yellow powder coat finish.

MODEL NUMBER	DESCRIPTION	HEIGHT	LENGTH	OUTSIDE DIAMETER	NET WT. (POUNDS)	
FSBOL-24	FLOOR STOP BOLLARD	5"	24"	4-1/2"	36/UPS	
FSBOL-36	FLOOR STOP BOLLARD	5"	36"	4-1/2"	47/UPS	
FSBOL-42	FLOOR STOP BOLLARD	5"	42"	4-1/2"	52/UPS	
FSBOL-48	FLOOR STOP BOLLARD	5"	48"	4-1/2"	58/UPS	

Adjustable Width Rack Guards

Protect the row ends of tandem pallet racking with this heavy-duty, welded steel adjustable rack guard. Slide in design has a variable length range of 62" to 108". Includes steel mounting plates with 1" diameter holes to safely secure unit to floor. Powder coated with safety yellow finish.

MODEL NUMBER	ADJUSTABLE LENGTH	HEIGHT	NET WT. (POUNDS)	
ARMG-24Ⓢ	62" to 108"	24"	203	
ARMG-ABKⓈ	CONCRETE ANCHOR BOLTS (12) 3/4" x 4"		4	

New

Multi-Purpose Barricades

These polyethylene plastic barricades can be linked together to enclose any shape or size area. They are lightweight, and fold away for easy storage. Made from durable polyethylene plastic, and are suitable for both indoor and outdoor applications. The barricades are easy to clean, and bright yellow for high impact. Permanent mold in graphics with caution sign as standard. Available in two and three panel units.

MODEL NUMBER	WIDTH OF EACH PANEL	HEIGHT	LENGTH	THICKNESS	NUMBER OF PANELS	NET WT. (POUNDS)	
HG-2F	37"	36"	74"	1"	2	15	
HG-3F	37"	36"	111"	1"	3	23	



Adjustable Steel Safety Railings

The Adjustable Railing can be used to create walking paths or as a sliding gate for continuous run handrail systems. 1 $\frac{3}{4}$ " square tubing is painted safety yellow for high visibility. Unit stands 42" high and has a 21" mid-rail. Optional 96" long toe board is available. Safety yellow powder coat finish.

MODEL NUMBER	DESCRIPTION	SERVICE RANGE	NET WT. (POUNDS)	
ASR-96	WITHOUT TOEBOARD	96" TO 168"	54	
ASR-96-4-TB	WITH 4" HIGH TOEBOARD	96" TO 168"	61	



Poly Barricades

The color of these barricades is ideal for applications where appearance is an issue. Displays well at municipalities, parks, amusement parks, and parking areas. Ideal for traffic and crowd control. Lightweight and easy to fill with liquid or sand for added weight. Features a 4" fill cap and 2" drain. Approximate filled weight is 520 pounds. Additional colors available.

MODEL NUMBER	LENGTH	DEPTH	HEIGHT	COLOR	FILL CAPACITY	NET WT. (POUNDS)	
VPC-6-ORANGE	72"	16"	35"	ORANGE	60 GAL.	70	
VPC-6G	72"	16"	35"	GRAY	60 GAL.	70	



Units can be interlocked when more than one unit is needed.



Traffic Cones

These durable all weather cones are constructed from 100% PVC for long life. Their construction prohibits fading, cracking. Will retain its shape for years of reliable service. All models feature one piece mold except model TC-30, which features a removable weighted bottom. High-visibility orange in color. Suffix -2R features two reflectors around the traffic cone.

MODEL NUMBER	DESCRIPTION	HEIGHT	BASE (W x L)	PIECES PER CARTON	NET WT. (LBS.)	
TC-30	ECONOMY	30 $\frac{3}{4}$ "	17 $\frac{3}{4}$ " x 17 $\frac{3}{4}$ "	5	17	
TC-28-HD-2R	HEAVY DUTY	27 $\frac{1}{2}$ "	14" x 14"	1	10	
TC-28-SD-2R	STANDARD DUTY	27 $\frac{1}{2}$ "	14" x 14"	1	6	
TC-28-SD	STANDARD DUTY	27 $\frac{1}{2}$ "	14" x 14"	1	6	
TC-18-SD	STANDARD DUTY	17 $\frac{3}{4}$ "	14" x 14"	1	4	



model TC-30




model TC-28-HD-2R

90° Triple Elbow Guards

Protect the corners of machinery, buildings, and offices. The 90° bend fits snug around corners to provide the ultimate protection against potential damage from fork trucks or other mobile equipment. Base plate size is 8" x 8". Welded steel construction. Powder coated safety yellow.


MODEL NUMBER	DESCRIPTION	HEIGHT	LENGTH	OUTSIDE DIAMETER	NET WT. (POUNDS)	
TEG-24-24-4	TRIPLE ELBOW GUARD	24"	24"	4 $\frac{1}{2}$ "	69	
TEG-24-36-4	TRIPLE ELBOW GUARD	36"	24"	4 $\frac{1}{2}$ "	82	
TEG-24-42-4	TRIPLE ELBOW GUARD	42"	24"	4 $\frac{1}{2}$ "	90	
TEG-30-24-4	TRIPLE ELBOW GUARD	24"	30"	4 $\frac{1}{2}$ "	74	
TEG-30-36-4	TRIPLE ELBOW GUARD	36"	30"	4 $\frac{1}{2}$ "	88	
TEG-30-42-4	TRIPLE ELBOW GUARD	42"	30"	4 $\frac{1}{2}$ "	95	
TEG-ABK	CONCRETE ANCHOR BOLTS (8) 3/4" x 4" (4-1/2" GUARDS)				4	



Triple Elbow Guards with Center Support

Heavy-duty welded steel construction includes three support legs for extra strength and protection. The 90° bend fits snug around corners to provide the ultimate protection against potential damage from fork trucks or other mobile equipment. Base plate size is 8" x 8" with 7/8" x 1 $\frac{1}{4}$ " slotted bolt holes. Manufactured from 2" diameter steel pipe. Powder coated safety yellow with black and yellow safety tape.

MODEL NUMBER	DESCRIPTION	HEIGHT	LENGTH	OUTSIDE DIAMETER	NET WT. (POUNDS)	
TEGC-24-24-2	TRIPLE ELBOW GUARD	24"	24"	2"	58	
TEGC-24-36-2	TRIPLE ELBOW GUARD	36"	24"	2"	69	
TEGC-24-42-2	TRIPLE ELBOW GUARD	42"	24"	2"	76	
TEGC-30-24-2	TRIPLE ELBOW GUARD	24"	30"	2"	63	
TEGC-30-36-2	TRIPLE ELBOW GUARD	36"	30"	2"	74	
TEGC-30-42-2	TRIPLE ELBOW GUARD	42"	30"	2"	80	





Individual Components are Installed On-Sight



Fits against walls to protect drains or piping



SINGLE RAIL STRAIGHT POST
model MG-SP-36-1



DOUBLE RAIL CORNER POST
model MG-CP-36-2



RAILING SECTION
series MG-R



WALL MOUNT
series MG-WP



Modular Guard Systems

Modular Guard System can be ordered to fit almost any application. Designed for quick and easy assembly. Railing sections are installed and secured to each post with a single bolt. Select from different railing lengths to custom fit your application. Railing systems are made from heavy-duty 3" square steel tubing. Wall mounting posts may be used to secure guard assembly to a wall. Durable safety yellow powder coat finish. Steel construction. All components sold separately.

RAILING SECTION					
MODEL NUMBER	EFFECTIVE LENGTH	OVERALL LENGTH	SQUARE TUBE (O.D.)	NET WT. (POUNDS)	
MG-R-4 [Ⓢ]	48"	56"	3"	26	
MG-R-6 [Ⓢ]	72"	80"	3"	38	
MG-R-8 [Ⓢ]	96"	104"	3"	49	
MG-R-10 [Ⓢ]	120"	128"	3"	60	
MG-R-12	144"	152"	3"	71	

MOUNTING POSTS					
MODEL NUMBER	DESCRIPTION	STYLE	OVERALL HEIGHT	NET WT. (POUNDS)	
MG-CP-36-1 [Ⓢ]	CORNER POST	SINGLE RAIL	36"	37	
MG-CP-36-2	CORNER POST	DOUBLE RAIL	36"	49	
MG-SP-36-1 [Ⓢ]	STRAIGHT POST	SINGLE RAIL	36"	37	
MG-SP-36-2	STRAIGHT POST	DOUBLE RAIL	36"	49	

MOUNTING OPTIONS			
MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)	
MG-WP-A [Ⓢ]	WALL MOUNTING POST - POST TUBING	7	
MG-WP-B [Ⓢ]	WALL MOUNTING POST - RAILING SECTION TUBING	8	
MG-KIT [Ⓢ]	CONCRETE ANCHOR BOLTS (4 ANCHORS)	4	

Heavy Duty Column Protectors

Two-piece design for protecting in-plant columns and other vertical support members. Hardware is included to connect both pieces together. Heavy-duty welded steel construction. Each base plate includes (4) pre-drilled mounting holes. Concrete installation hardware sold separately. Powder coat safety yellow finish.

MODEL NUMBER	HEIGHT	INSIDE WIDTH	INSIDE LENGTH	NET WT. (POUNDS)	
CGP-24	24"	20"	20"	132	
CGP-36	36"	20"	20"	150	
CGP-48	48"	20"	20"	168	
CGP-ABK	CONCRETE ANCHOR BOLTS (8) 3/4" x 4"			4	

Gantry/Jib Guard

Prevent costly damage to steel columns, pipe, and tubing from carts and fork trucks. Solid steel design is constructed of 1/2" thick material for maximum strength. Ideal for fixed jibs and gantry cranes. Mounting plate measures 16" wide by 13 1/2" deep and features (6) pre-drilled mounting holes.

MODEL NUMBER	INSIDE WIDTH	INSIDE DEPTH	OVERALL HEIGHT	NET WT. (POUNDS)	
CG-42 [Ⓢ]	10-1/4"	10-1/8"	42"	150	
CG-ABK	CONCRETE ANCHOR BOLTS (6) 3/4" x 4"			4	



Structural Column Protectors

Provide wrap around protection to columns, pipes, and tubing to prevent damage. Constructed of UV protected polyethylene. Units can be stacked two high. Easy to assemble with fasteners included.

MODEL NUMBER	INSIDE OPENING	OUTSIDE WIDTH	OVERALL HEIGHT	CAPACITY (POUNDS)	NET WT. (POUNDS)	
HEAVY DUTY						
VB-6	6" SQUARE	26"	42"	7000 @ 6 MPH	46	
VB-8	8" SQUARE	26"	42"	7000 @ 6 MPH	46	
VB-10	10" SQUARE	26"	42"	7000 @ 6 MPH	46	
VB-12	12" SQUARE	26"	42"	7000 @ 6 MPH	46	
VB-8-10	8" x 10" RECTANGLE	26"	42"	7000 @ 6 MPH	46	
VB-9R	9" ROUND	26"	42"	7000 @ 6 MPH	46	
MEDIUM DUTY						
VPUP-6	6" SQUARE	24"	24"	7000 @ 6 MPH	28	
VPUP-8	8" SQUARE	24"	24"	7000 @ 6 MPH	28	
VPUP-10	10" SQUARE	24"	24"	7000 @ 6 MPH	28	
VPUP-12	12" SQUARE	24"	24"	7000 @ 6 MPH	28	
LIGHT DUTY						
VBS-3	3" SQUARE	12"	42"	7000 @ 6 MPH	18	
VBS-4	4" SQUARE	12"	42"	7000 @ 6 MPH	18	
VBS-5	5" SQUARE	12"	42"	7000 @ 6 MPH	18	
VBS-6	6" SQUARE	12"	42"	7000 @ 6 MPH	18	



Bumper Wrap

Bumper Wrap is a flexible UV coated protective wrap for use in warehouses, drive-thru's, fueling stations, and municipal barrier applications. Made of a non-marring, highly visible, flexible vinyl. Protect vehicles from impact and scraping damage while protecting posts from constant abuse.

MODEL NUMBER	DESCRIPTION	OVERALL HEIGHT	THICKNESS	NET WT. (POUNDS)	
BW-480	40 FOOT BULK ROLL	12"	3/8"	53	
BW-TIE-24	(4) 24" CABLE TIE			1	
BW-TIE-36	(4) 36" CABLE TIE			1	
BW-TIE-48	(4) 48" CABLE TIE			1	



Light Pole Base Protectors

Quickly and inexpensively enhance the visual appearance of your parking lot, lower your long term maintenance costs, while offering safety to your customers and their cars. Designed to fit around a 24" diameter light pole base. The ring assembly allows it to fit any height, and the top is easily customized to fit round or square light poles. Each ring is 9½" high. Unit comes in half circles that are snapped together around the base and then stacked on top of each other. These are easily installed, without the use of tools. **When ordering specify; color, height, and light pole diameter for top piece.**



MODEL NUMBER	MATERIAL	CEMENT BASE DIAMETER	OVERALL HEIGHT	NET WT. (POUNDS)	
LPBP-24	POLYPROPYLENE	24"	ANY	25	

SPECIFY COLOR WHEN ORDERING					
COLOR		COLOR		COLOR	
	CAUTION RED		HUNTER GREEN		BROWN
	SAFETY BLUE		ORANGE		STONE GRAY
	SAFETY YELLOW		IMPERIAL BLUE		BLACK





Surface Mount Flexible Stakes

Ideal for high traffic and high impact locations. Constructed of polycarbonate extrusion and flexible hinge which makes it virtually indestructible. Easy four part assembly which is the post and hinge, base, grips and pin. Quick to install, they can be mounted to concrete, asphalt, wood and other hard surfaces using appropriate hardware (not included). FAA approved. Other colors and styles are available.

MODEL NUMBER	DESCRIPTION	OVERALL HEIGHT	WIDTH	COLOR	NET WT. (POUNDS)	
VGLT-16-2F-W	FLEXIBLE STAKE	24"	3 1/4"	WHITE	3	
VGLT-16-2F-Y	FLEXIBLE STAKE	24"	3 1/4"	YELLOW	3	
VGLT-16-2F-O	FLEXIBLE STAKE	24"	3 1/4"	ORANGE	3	
VGLT-16-3F-W	FLEXIBLE STAKE	36"	3 1/4"	WHITE	3.5	
VGLT-16-3F-Y	FLEXIBLE STAKE	36"	3 1/4"	YELLOW	3.5	
VGLT-16-3F-O	FLEXIBLE STAKE	36"	3 1/4"	ORANGE	3.5	
VGLT-16-4F-W	FLEXIBLE STAKE	48"	3 1/4"	WHITE	4	
VGLT-16-4F-Y	FLEXIBLE STAKE	48"	3 1/4"	YELLOW	4	
VGLT-16-4F-O	FLEXIBLE STAKE	48"	3 1/4"	ORANGE	4	
VGLT-RT-W*	REFLECTIVE SHEETING	6"	3"	WHITE	0.5	
VGLT-RT-Y*	REFLECTIVE SHEETING	6"	3"	YELLOW	0.5	
VGLT-RT-O*	REFLECTIVE SHEETING	6"	3"	ORANGE	0.5	

*SOLD EACH / ONE PER SIDE



model VPP-5R



model DSG-48



Pipe and Downspout Protectors

Protect down spouts and pipes attached to buildings from damage caused by fork trucks, vehicles, and mowers. Our Steel Down Spout Guards fit around standard down spouts. The Poly Pipe Protector fits pipes up to 5" diameter. Easy bolt on installation - installation hardware not included. Choose steel for optimum strength or polyethylene for protection with deflection. Steel model is powder coated safety yellow.

MODEL NUMBER	MATERIAL	INSIDE (W x D)	OVERALL SIZE (W x D x H)	NET WT. (POUNDS)	
VPP-5R	POLYETHYLENE	5" x 5"	12" x 6" x 42"	6	
DSG-48*	STEEL	6" x 6"	10" x 6 1/2" x 42"	63	

Polyethylene Rack Protector

Protect pallet racking from damage with rugged polyethylene protectors. Easy installation with quick velcro mount or concrete lag to the ground hardware included. Safety yellow color increases visibility.

MODEL NUMBER	MATERIAL	USABLE OPENING SIZE	OVERALL SIZE (W x L x H)	NET WT. (POUNDS)	
VRP-18	POLYETHYLENE	3 1/2"	4 1/2" x 8" x 18"	3	



model VRP-18



series VPRP

Rack Shield

Easy one-step installation, this Rack Shield eliminates painting and prevents damage to your vertical supports. Made of extruded high-density polyethylene thermoplastic.

MODEL NUMBER	OVERALL HEIGHT	USABLE SIZE (W x D)	HWDR. KITS REQUIRED	COLOR	NET WT. (LBS.)	
VPRP-YL-09	9"	3" x 2"	1	YELLOW	1 1/2	
VPRP-YL-12	12"	3" x 2"	2	YELLOW	2	
VPRP-YL-18	18"	3" x 2"	2	YELLOW	3 1/2	
VPRP-HDWR	HARDWARE KIT (1) 3/8" x 3" BOLTS				1	

AVAILABLE IN GRAY AND BLACK, CONTACT FACTORY

Poly Rack Guards

Poly Rack Guards are a new innovation offering exceptional performance in racking protection. Rack systems are not designed to be struck by fork-lifts and even low speed collisions can lead to structural damage. This damage is a major occupational health and safety issue and is very costly to repair. Installation takes just seconds to install by hand. The design incorporates an ingenious spring clip design that enables it to securely grip the column and automatically adjust its width to suit a wide range of column sizes. All other products require an additional attachment system like Velcro, bolts, concrete penetration or additional parts that are prone to breakage.

MODEL NUMBER	OVERALL HEIGHT	FITS COLUMNS MEASURING	COLOR*	NET WT. (POUNDS)	
PRG-5-1	5.24"	3" x 1-5/8"	YELLOW OR BLACK	3	
PRG-5-2	5.24"	3-1/4" x 2"	YELLOW OR BLACK	3	
PRG-5-3	5.24"	3" x 3"	YELLOW OR BLACK	3	

*SPECIFY COLOR WHEN ORDERING - YELLOW OR BLACK



Low Profile Rack Guards

Protect pallet racking and wall corners against damage from fork trucks, pallet trucks, and carts with Low Profile Rack Guards. All components are laser cut. Quick and easy two-hole installation. Installs in half the time of other guards. Safety yellow powder coat finish. Steel construction. Mounting kit sold separately.

MODEL NUMBER	OVERALL HEIGHT	USABLE OPENING (W x D)	OVERALL BASE (W x D)	NET WT. (POUNDS)	
NPG4-12 [Ⓢ]	12"	4¼" x 1"	8" x 3"	8	
NPG4-18 [Ⓢ]	18"	4¼" x 1"	8" x 3"	12	
NPG4-24 [Ⓢ]	24"	4¼" x 1"	8" x 3"	16	
NPG4-36 [Ⓢ]	36"	4¼" x 1"	8" x 3"	18	
NPG6-12 [Ⓢ]	12"	6¼" x 1"	10" x 3"	9	
NPG6-18 [Ⓢ]	18"	6¼" x 1"	10" x 3"	13	
NPG6-24 [Ⓢ]	24"	6¼" x 1"	10" x 3"	15	
NPG6-36 [Ⓢ]	36"	6¼" x 1"	10" x 3"	20	
NPG-ABK [Ⓢ]	CONCRETE ANCHOR BOLTS (2) 3/4" x 4"			2	



LOW PROFILE RACK GUARDS
series NPG



Structural Cast Rack Guards

Economical way to protect against damage to pallet racking and wall corners. Constructed of 6" cast steel for durability. Available with or without a rubber bumper. Easy to install to concrete surface. Four mounting holes for maximum stability. Safety yellow powder coat finish. Installation hardware sold separately.



STRUCTURAL CAST RACK GUARDS					
MODEL NUMBER	OVERALL HEIGHT	USABLE OPENING (W x D)	OVERALL BASE (W x D)	NET WT. (POUNDS)	
G6-12 [Ⓢ]	12"	4½" x 4"	10½" x 6¼"	11	
G6-18 [Ⓢ]	18"	4½" x 4"	10½" x 6¼"	20	
G6-24 [Ⓢ]	24"	4½" x 4"	10½" x 6¼"	26	
G6-36 [Ⓢ]	36"	4½" x 4"	10½" x 6¼"	34	
G8-12 [Ⓢ]	12"	6½" x 4"	12½" x 6¼"	13	
G8-18 [Ⓢ]	18"	6½" x 4"	12½" x 6¼"	24	
G8-24 [Ⓢ]	24"	6½" x 4"	12½" x 6¼"	36	
G8-36 [Ⓢ]	36"	6½" x 4"	12½" x 6¼"	42	
STRUCTURAL CAST RACK GUARDS WITH RUBBER BUMPERS					
G6-12-B	12"	4½" x 4"	10½" x 8¼"	18	
G6-18-B	18"	4½" x 4"	10½" x 8¼"	30	
G6-24-B	24"	4½" x 4"	10½" x 8¼"	39	
G6-36-B	36"	4½" x 4"	10½" x 8¼"	48	
G8-12-B	12"	6½" x 4"	12½" x 8¼"	20	
G8-18-B	18"	6½" x 4"	12½" x 8¼"	34	
G8-24-B	24"	6½" x 4"	12½" x 8¼"	47	
G8-36-B	36"	6½" x 4"	12½" x 8¼"	56	
G-ABK [Ⓢ]	CONCRETE ANCHOR BOLTS (4) ¾" x 4"			4	



CAST RACK GUARDS
series G6



CAST RACK GUARDS
series G8



CAST RACK GUARDS
WITH RUBBER BUMPERS
series G6-B



CAST RACK GUARDS
WITH RUBBER BUMPERS
series G8-B

Rack Guard with Rubber Bumper Insert

Protect pallet racking with durable wrap around protection. Increase pallet rack column strength on impact by over 100%. Includes rubber bumper insert, ½" thick, and hardware. Easy to install with wrench or socket. No concrete drilling required. Steel construction. Powder coat safety yellow finish.

MODEL NUMBER	OVERALL SIZE (W x D)	USABLE OPENING (W x D) W/BUMPER	OVERALL HEIGHT	NET WT. (POUNDS)	
RUD-24 [Ⓢ]	3⅜" x 4⅞"	3⅞" x 3⅝"	24"	19	




Corner Guards

Protect busy corners, expensive machinery and personnel with 90° perpendicular protection. "SAFETY FIRST" promotion reminds personnel of the number one priority. Steel units include powder coat safety yellow finish. Aluminum unit is unfinished.

MODEL NUMBER	OVERALL HEIGHT	OVERALL LENGTH	SIDE HEIGHT	MATERIAL	NET WT. (POUNDS)	
PCG-16 [Ⓢ]	16"	16"	8"	STEEL	30	
PCG-24 [Ⓢ]	24"	24"	12"	STEEL	35	
PCG-24-A	24"	24"	12"	ALUMINUM	18	
PCG-ABK [Ⓢ]	CONCRETE ANCHOR BOLTS (3) 3/4" x 4"				2	





RCP-B-BY VCP-40 MRCG-20 MRCG-39

Corner Protectors

Heavy-duty corner protectors are designed to protect corners from damage. Extremely versatile protection for in warehouses, offices, overhead door frames and tracks, or any 90° corner.

Rubber Corner Protector, model RCP-B-BY, features black and yellow stripes for increased visibility. Includes (6) mounting holes to secure unit to wall. Hole diameter is 3/16".

Corner Protector, model VCP-40, is made of shock absorbing molded polyethylene construction. 2 1/4" thick with one flange edge measuring 6" and the other 8".

Molded Rubber Corner Protectors, series MRCG, are made from black molded rubber. A corner protector includes reflective safety yellow tape for higher visibility.

MODEL NUMBER	OVERALL HEIGHT	FLANGE WIDTH	DRYWALL ANCHORS	MATERIAL	NET WT. (POUNDS)	
RCP-B-BY	35 1/2"	3"	INCLUDED	RUBBER	6	
VCP-40	40 1/2"	6" & 8"	NOT INCLUDED	POLY	3	
MRCG-20	20"	5 1/2"	NOT INCLUDED	RUBBER	5	
MRCG-39	39"	6"	NOT INCLUDED	RUBBER	8	



Polyethylene Wall Protector

Protect building walls from scratches and dents. This wall protector is weather resistant for use both indoors and outdoors. Constructed of molded polyethylene material. Safety yellow for high visibility. Features 3/8" counter sunk holes for anchor bolts. Hardware not included.

MODEL NUMBER	DESCRIPTION	OVERALL (W x H)	PROJECTION	NET WT. (POUNDS)	
VBG-48	POLYETHYLENE	48" x 6 1/4"	2 1/4"	6	

Overhead Door Track Protectors

Protect the tracks of overhead doors from fork trucks, pallet trucks, and other traffic with these solid steel constructed, economical Overhead Door Track Protectors. The base plate is 6" square with a 3" notch out and 9/16" diameter mounting holes. Safety yellow powder coat finish for long term wear. Steel construction.

MODEL NUMBER	HEIGHT	BASE PLATE SPECIFICATIONS	MOUNTING HOLE DIAMETER	NET WT. (POUNDS)	
DSP-24	24"	6" Square 3" Notch Out	9/16"	13	
DSP-36	36"	6" Square 3" Notch Out	9/16"	20	
DSP-48	48"	6" Square 3" Notch Out	9/16"	27	
DSP-ABK	CONCRETE ANCHOR BOLTS (3) 3/8" x 4"			3	



Economical Overhead Door Warning Barriers

Protect overhead doors from fork trucks and other traffic coming and going throughout each day. Intended for use as a warning system - not a fork truck stop. Constructed with tubular steel uprights and a 4" x 4" wooden beam across the top of the guard. The wooden beam can be easily and inexpensively replaced when damaged. Guard will not interfere with overhead door. Complete unit is painted high visibility OSHA safety yellow. Concrete installation kit available. Custom sizes available.

MODEL NUMBER	USABLE DOOR WIDTH (FT.)	USABLE DOOR HEIGHT (FT.)	COLOR	NET WT. (POUNDS)	
DWB-88	8	8	YELLOW	395	
DWB-810	8	10	YELLOW	475	
DWB-910	9	10	YELLOW	490	
DWB-1010	10	10	YELLOW	505	
DWB-ABK	CONCRETE ANCHOR BOLTS (8) 3/4" x 6"			10	



Downspout Drain Water Disperser

Attaches to most standard down spouts. Easy installation, fits up and around the end of downspout. During a rainstorm water collects at the bottom of drains, ruining grass and landscaping. This device evenly disperses the water outward over a larger area. Constructed of aluminum. Installation hardware not included.

MODEL NUMBER	OVERALL HEIGHT	OVERALL WIDTH	DEPTH	NET WT. (POUNDS)	
DRAIN-DD	6 1/2"	6"	8"	6	



Overhead Door Warning Barriers

Protect overhead doors from fork truck damage. Heavy-duty PVC construction is lightweight and will not rust. Highly visible black and yellow safety tape and two American flags serve as a visual warning. Includes two 15' long chains with quick connects to hang barrier from ceiling or existing overhead door track.

Model ODG-133-BL features built-in warning sirens and flashing lights that activate when the barrier is bumped or contacted. Provides for an audible and visual warning before damage to overhead door is caused. Requires (2) 9V lithium batteries, not included.

MODEL NUMBER	DESCRIPTION	OVERALL LENGTH	NET WT. (POUNDS)	
ODG-121-F	ECONOMY WARNING BARRIER	120"	40	
ODG-133-BL	DELUXE WARNING BARRIER	133"	45	



ECONOMY WARNING BARRIER • model ODG-121-F



DELUXE WARNING BARRIER • model ODG-133-BL

Automatic Overhead Door Lock

Unique product will allow overhead doors to be locked in virtually any up position. Automatically locks doors in full up position or in the closed position. Prevents the overhead door from unexpectedly "slamming down". Protects personnel, product, and equipment. Spring-loaded locking latch is released by pulling rope (included). Simply bolts to any overhead door (installation hardware is not included). Includes two reversible "locking plates" that may be mounted anywhere along door track. Heavy-duty welded steel construction with yellow painted finish.

MODEL NUMBER	DESCRIPTION	COLOR	NET WT. (POUNDS)	
DR-LOCK	OVERHEAD DOOR LOCK	YELLOW	10	



Mezzanine Safety Gate

The Mezzanine Safety Gate provides an OSHA required 42" high handrail, 21" high mid-rail and 4" high kickplate for mezzanines without sacrificing load accessibility. The gate rotates to allow a usable area of 58"W x 76"H x 70"D. Gate design is balanced to allow for easy operation without use of springs. Safety yellow powder coat finish. Welded steel construction.

MODEL NUMBER	OVERALL HEIGHT	OVERALL WIDTH	OVERALL DEPTH	USABLE WIDTH	NET WT. (POUNDS)	
MEZZ-200	79½"	68½"	76"	58"	230	



DVD or VIDEO AVAILABLE



Expand-A-Gate

Designed to set up quickly and easily wherever and whenever they are needed. Ideal for preventing potential accidents. Lightweight design allows personnel to quickly retrieve the gate and limit access to unsafe areas. Smooth operating scissor action. Interlocking and nestable. Steel or aluminum construction available. Suffix -C features casters.

MODEL NUMBER	COLLAPSED WIDTH	EXPANDED WIDTH	*OVERALL HEIGHT	NET WT. (POUNDS)	
STEEL CONSTRUCTION					
EXGATE-30	14½"	144"	37"	36	
EXGATE-30-C	14½"	144"	43"	54	
ALUMINUM CONSTRUCTION					
ALEXGATE	14½"	144"	37"	22	
ALEXGATE-30-C	14½"	144"	43"	30	

*OVERALL HEIGHT WHEN COLLAPSED




Galvanized Door Scissor Gates

Prevent access to rooms with standard pedestrian Door Scissor Gates. Ideal for department store door openings, offices, warehouse inventory rooms, etc. Steel construction. Installation hardware not included.

MODEL NUMBER	*MAXIMUM HEIGHT	MAXIMUM WIDTH	NET WT. (POUNDS)	
VD-63	63"	48"	42	
VD-68	66"	48"	54	
VD-73	73"	48"	56	
VD-79	79"	48"	60	
VD-81	81"	48"	61	
VD-83	83"	48"	62	

*MAXIMUM HEIGHT WHEN COLLAPSED



Galvanized Folding Gates

Secure outside access during the day and add security at night with heavy-duty 15 gauge steel folding gates. Durable 3" steel wheels allow operator to quickly and fully retract gate when not in use. Center drop pin rests in pre-drilled hole to secure gate when extended. Easy installation! Lock is located on right side on single gates. Galvanized for durability. Constructed of steel U-channels riveted back to back using aircraft quality rivets and heavy-duty 1½" x 1½" vertical angles. Installation hardware included. Contact factory for additional sizes.



CENTER DROP PIN



CENTER DROP PIN

PROTECTIVE BARRIERS

SINGLE FOLDING GATES					
MODEL NUMBER	USABLE WIDTH (FEET)	COLLAPSED HEIGHT (FEET)	IN USE HEIGHT (FEET)	NET WEIGHT (POUNDS)	
VSSG-465*	3 to 4	6½	6	69	
VSSG-470*		7	6½	73	
VSSG-475		7½	7	77	
VSSG-480		8	7½	80	
VSSG-485		8½	8	84	
VSSG-565*	4 to 5	6½	6	73	
VSSG-570*		7	6½	74	
VSSG-575		7½	7	78	
VSSG-580		8	7½	80	
VSSG-585		8½	8	82	
VSSG-665*	5 to 6	6½	6	76	
VSSG-670*		7	6½	79	
VSSG-675		7½	7	81	
VSSG-680		8	7½	84	
VSSG-685		8½	8	86	
VSSG-765*	6 to 7	6½	6	82	
VSSG-770*		7	6½	85	
VSSG-775		7½	7	87	
VSSG-780		8	7½	90	
VSSG-785		8½	8	92	
VSSG-865*	7 to 8	6½	6	88	
VSSG-870*		7	6½	92	
VSSG-875		7½	7	96	
VSSG-880		8	7½	99	
VSSG-885		8½	8	104	
VSSG-970	8 to 9	7	6½	102	
VSSG-975		7½	7	104	
VSSG-980		8	7½	106	
VSSG-1070	9 to 10	7	6½	109	
VSSG-1080		8	7½	112	

DOUBLE FOLDING GATES					
MODEL NUMBER	USABLE WIDTH (FEET)	COLLAPSED HEIGHT (FEET)	IN USE HEIGHT (FEET)	NET WEIGHT (POUNDS)	
VPFG-865*	6 to 8	6½	6	120	
VPFG-870*		7	6½	124	
VPFG-875		7½	7	129	
VPFG-880		8	7½	134	
VPFG-885		8½	8	139	
VPFG-1065*	8 to 10	6½	6	144	
VPFG-1070*		7	6½	148	
VPFG-1075		7½	7	153	
VPFG-1080		8	7½	158	
VPFG-1085		8½	8	162	
VPFG-1265*	10 to 12	6½	6	168	
VPFG-1270*		7	6½	172	
VPFG-1275		7½	7	177	
VPFG-1280		8	7½	182	
VPFG-1285		8½	8	187	
VPFG-1465*	12 to 14	6½	6	180	
VPFG-1470*		7	6½	184	
VPFG-1475		7½	7	189	
VPFG-1480		8	7½	196	
VPFG-1485		8½	8	199	
VPFG-1665*	14 to 16	6½	6	192	
VPFG-1670*		7	6½	196	
VPFG-1675		7½	7	199	
VPFG-1680		8	7½	201	
VPFG-1685		8½	8	206	
VPFG-1870	16 to 18	7	6½	204	
VPFG-1875		7½	7½	208	
VPFG-1880		8	7	211	
VPFG-2070	18 to 20	7	6½	216	
VPFG-2080		8	7½	230	



Galvanized Portable Gate

Gates are perfect for many locations; hospitals, schools, and warehouses. Use for blocking equipment, personnel, and entrances. Portable gates expand and lock to close off any opening which allows for mobile safety and security. When not in use simply fold up, roll away, and store. Purchase optional add-on sections to expand to any distance.

MODEL NUMBER	COLLAPSED WIDTH	EXPANDED WIDTH	COLLAPSED HEIGHT	USABLE HEIGHT	CASTER STYLE	NET WT. (POUNDS)	
VXL-1265	78"	144"	79½"	73½"	3" RUBBER	144	
VXL-665	ADD-ON SECTION 6 FEET LONG WHEN EXPANDED					72	