



Trailer Stabilizing Jacks

Jacks are used to prevent up-ending semi-trailers when they are not connected to a tractor during loading and unloading operations. Also used to level trailers parked on sloped ground and to prevent landing gear from sinking into a soft surface. High strength steel construction. Flush-type zerk fitting for lubricating ACME screw. Meets OSHA regulations when used with wheel chocks. Powder coat safety yellow finish. Includes reflective collar for visibility at night.



model SJS-1012



model SAJ-1012

TYPE	MODEL NUMBER	DESCRIPTION	STATIC CAPACITY (LBS)	LIFTING CAPACITY (LBS)	SERVICE RANGE	WHEEL SIZE & TYPE	NET WT. (LBS.)
A	BFSJ-2748	BIG FOOT JACK	100,000	40,000	39½" to 51"	10" hard rubber	125
B	LO-J-BEAM	RATCHET BEAM	100,000	40,000	39½" to 51"	10" x 2" hard rubber	160
C	SP-TOP-BEAM	RATCHET BEAM	100,000	40,000	39½" to 51"	10" x 2" hard rubber	160
D	H-LO-J-BEAM	HYDRAULIC BEAM	100,000	40,000	41" to 47"	10" x 2" hard rubber	228
E	CJ-BEAM-SN	HAND CRANK	100,000	50,000	41" to 55"	16" solid foam	210
E	CJ-BEAM-PN	HAND CRANK	100,000	50,000	41" to 55"	16" fully pneumatic	210
F	LO-J	RATCHET	100,000	40,000	39" to 51"	10" hard rubber	110
G	HI-J	RATCHET	100,000	40,000	45" to 57"	10" hard rubber	115
H	SP-TOP	SPIN TOP	100,000	40,000	39½" to 51"	10" hard rubber	110
I	SP-TOP-R	RATCHET	100,000	40,000	41" to 50"	10" hard rubber	115
J	SJ-35	ECONOMY	50,000	5,000	44" to 51"	N/A	45/UPS
K	SJ-35-2-H	ECONOMY	50,000	5,000	44" to 51"	N/A	45/UPS
L	SJ-35-EF	ECONOMY	50,000	5,000	41" to 57½"	8" hard rubber	60

TRAILER STABILIZING JACK OPTIONS

MODEL NUMBER	DESCRIPTION	NET WT. (LBS.)
JACK-100	50,000 POUNDS LIFTING CAPACITY (NOT AVAILABLE ON SJ series)	18
SJS-1012	ALUMINUM STABILIZING JACK TRAILER INSTRUCTION SIGN	1
SAJ-1012	ALUMINUM DRIVERS BEWARE INSTRUCTION SIGN	1